



## SPECIFICATIONS

### KOAT-A-ROLL® POLYURETHANE ROLLER SLEEVES MAXIMUM TEMPERATURE 170°

#### 83 Shore A Orange Polyurethane

Fits Roller O.D.	Wall Thickness	Part #
1.00	1/8 in.	K-1.00
1.37	1/8 in.	K-1.37
1.62	1/8 in.	K-1.62
1.75	1/8 in.	K-1.75
1.90	1/16 in.	K-1.90/.06
1.90	1/8 in.	K-1.90
1.90	1/4 in.	K-1.90/.25
2.00	1/8 in.	K-2.00
2.25	1/8 in.	K-2.25
2.37	1/8 in.	K-2.37
2.50	1/8 in.	K-2.50
2.50	1/4 in.	K-2.50/.25
2.75	1/8 in.	K-2.75
3.00	1/8 in.	K-3.00
3.25	1/8 in.	K-3.25
3.50	1/8 in.	K-3.50
4.00	1/8 in.	K-4.00

#### 83 Shore A Black Polyurethane

Fits Roller O.D.	Wall Thickness	Part #
1.37	1/8 in.	K-1.37BLK
1.62	1/8 in.	K-1.62BLK
1.90	1/8 in.	K-1.90BLK
2.00	1/8 in.	K-2.00BLK
2.50	1/8 in.	K-2.50BLK

#### 83 Shore A Green Polyurethane

Fits Roller O.D.	Wall Thickness	Part #
1.37	1/8 in.	K-1.37GRN
1.62	1/8 in.	K-1.62GRN
1.90	1/8 in.	K-1.90GRN

Stocked in 10 ft lengths for immediate delivery. Custom colors, hardnesses and materials are available by special order. Koat-A-Roll can be cut to length or factory installed on your rolls at our facility or we will cut and/or install them for you. Call for special pricing and availability